



CB

(Dispenser not included)

- The Commercial Barista series meets the growing demand for high quality and volume brewing profiles.
- The Commercial Barista series controls three vital aspects in brewing: water temperature, water volume, and water contact time.
- Integrated features such as: "Brew 1" & "Brew 2" selector buttons, water volume adjustment via digital display, water temperature adjustment via digital display, pre-infusion, pulse brewing, water filtering indicator light, filter monitor, audible signals, service indicator light, coffee monitor light, cycle counter, and power conservation.



No Manuals Available

- The Commercial Barista series are made up of four of brewers configured in the 120v/240v dual voltage specification designed to brew into high volume thermal containers. The series brewing configuration is based on the numbers "0" – thermal dispensers without base, "2" – thermal server without base: large capacity, "5" – thermal airports, and "7" – thermal dispensers with base.

Dispenser Options:

Width 9 1/2"
Length: 20 3/4"
Height: 27 1/8"

| Base Model | Part Number | Volts | Amps | Tank Wattage | Cubic Feet | Ship Weight | Cord Attached |
|------------|-------------|-------|-------|--------------|------------|-------------|---------------|
| CB | | 240 | 22.92 | 5500w | 5.86 | 34 lbs | No |

Electrical: 120V models are 2 wires plus ground services rated 120V, single phase, 60 Hz.
 120/240V models are 3 wires plus ground service rated 120/240V, single phase, 60 Hz.

Plumbing: Water line should be 20-90 PSI and have a minimum flow rate of 1.5 GPM.
 Mechanical connection on brewer is 1/4" male flare connector.