



TVT Tea Brewer

(Pictured with Optional hot water faucet)

- Digital Electronics allows brewing up to 3 independent beverage volumes, with the ability to enhance the taste profile of the beverage by adjusting the brewing temperature and the water contact time with or without water bypassing.
- Simplex programming, with TVT technology, all you need to know is *How Much Total Volume*How Much Coffee*How Long To Brew* and you have programmed your recipe.
- Brewer incorporates patented base design which allows for height adjustability.
- Auto Arm system will not brew until the hot water has reach the correct brewing temperature.
- Vis A Brew - Brewing alert system is adjustable from 3 independent times to match the brewing process you select.



PDF Manuals & Files:



- Brew Capacities: 30 ounces up to 5 gallons
- 3 independent brew buttons can be customized with product labels for ease of brewing.
- Stainless Steel construction, with back up pour over feature.
- Patent pending
- Dual Voltage 120/240V

Dispenser Options:



Low Profile (GXF-P Models)

Width 9 1/2"
Length: 20 1/4"
Height: 24 3/4"

Tall Profile (GXF-8D Models)

Width 9 1/2"
Length: 20 1/4"
Height: 32 3/16"

Dispenser choices differ depending on tall or short brewer

Base Model	Part Number	Volts	Amps	Tank Wattage*	Cubic Feet	Ship Weight	Cord Attached
GXF-8D	701014	120	11.7	1375w	9.8	46lbs	Yes
GXF-8D	701060	120/240	23.1	5500w	9.8	46lbs	No
GXF-P	701054	120	11.7	1375w	7.3	42lbs	Yes
GXF-P	701057	120/240	23.1	5500w	7.3	42lbs	No

*Other wattages available. Please inquire when placing your order

Electrical: 120V models are 2 wires plus ground services rated 120V, single phase, 60 Hz.
 120/240V models are 3 wires plus ground service rated 120/240V, single phase, 60 Hz.

Plumbing: Water line should be 20-90 PSI and have a minimum flow rate of 1.5 GPM.
 Mechanical connection on brewer is 1/4" male flare connector.