



# Hot Water Machine

(Dispenser not included)

- **Dual Voltage:** Convertible for 110 or 220 voltage applications for site flexibility and inventory management
- **TVT Programming Technology** Leading edge digital programming from Newco allows for easier set up and operational accuracy
- **Large LCD Display** Quick referencing of system settings for efficient operator management
- **Self Monitoring** 6 potential error modes and dual zone temperature readout indicate system status for convenience of operation and pre-service trouble shooting
- **Advanced Temperature Control** dual thermistors (top and bottom) ensure consistent temperature draw throughout the tank
- **Automatic Pre-Fill** fills on initial hook up for convenience of install. Element is activated only when water level has reached the top probe



PDF Manuals & Files:



- **Durability** Stainless steel exterior and tank assembly
- **Standard Drip Tray** Large capacity drip tray with logoed stainless steel cover for durability and esthetic appeal
- **Bold Caution Decal** Bi-lingual "CAUTION VERY HOT WATER" decal reinforces operator safety and awareness
- **Capacity** 2 gallon Tank

**Width** 7.02"  
**Length:** 8.63"  
**Height:** 24.08"

<b>Base Model</b>	<b>Part Number</b>	<b>Volts</b>	<b>Amps</b>	<b>Tank Wattage</b>	<b>Cubic Feet</b>	<b>Ship Weight</b>	<b>Cord Attached</b>
NHW-15	104100	120	13.75	1650w	.976	20lbs	Yes
NHW-15	104100	240	27.50	6600w	.976	20lbs	No

**Electrical:** 120V models are 2 wires plus ground services rated 120V, single phase, 60 Hz.  
120/240V models are 3 wires plus ground service rated 120/240V, single phase, 60 Hz.

**Plumbing:** Water line should be 20-90 PSI and have a minimum flow rate of 1.5 GPM.  
Mechanical connection on brewer is 1/4" male flare connector.